

LVTS-51.2V 200AH Power Wall Lithium Battery





Excellent BMS System

PAC Brand BMS, Vehicle specification level BMS board, High stability and intelligence with various protection.

Minimal installation


Easy install. Fast connection with Pylontech Connector(35mm²/8MM)


Long Life Service

15-20 years design service life, 5 years supplier warranty, 6000 times cycle life with 80% DOD

Real Smart

Perfectly communicate with Deye, Luxpower .etc inverter, Smart Charged and Management by inverter via the communication between inverter and battery. Compatible with most of inverter in the market.







LVTOPSUN POWER WALL 51.2V 200AH

Battery Specification	
Model	LVTS-10KWH200AH
Nominal Voltage	51.2v
Combination	16S4P
Capacity	200AH
Energy	10.24kwh
Dimensions	680x480x180(220)mm
Weight	96kg
Life time	Design service life 15-20 years, 5years warranty
Cycles(80%DOD)	6000 Cycles
Operation temperature	Charge: 0-45°C, Discharge: -20°C-55°C
Storage temperature	Keep at -20 to 65°C
Protection standard	IP21
Operation Voltage	44.8vdc-56.5vdc
Max charge voltage	56.5vdc
Max charge & discharge current	100A
Max power	10240W
Compatibility	Compatible with all standard inverter and charge controllers. Can do COMMUNICATION with DEYE & LUXPOWER.
Remarks	Battery must be wired in parallel only. If in series will void the warranty.